

# SLOAN FIXED BOLLARD M50/P2


SET & POUR BOLLARD - MODEL FB-2050

CRASH TESTED TO ASTM F2656-07 - M50/P2 RATED - STOPS 15,000 LB. VEHICLE AT 50 MPH IMPACT

## TYPICAL SINGLE BOLLARD INSTALLATION

### KEY FEATURES:

1. PREFABRICATED BOLLARD UNIT
2. NO REBAR IN FOUNDATION
3. BOLLARD SYSTEM CAN ACCOMMODATE TURNING RADIUS



6828 W Melrose St.  
Boise, ID 83709  
Phone: 1-800-275-5998  
Email: info@sloansg.com  
Web: www.sloansg.com

**PATENT PROTECTED**

**THE DRAWINGS AND INFORMATION CONTAINED HEREIN ARE PROPRIETARY AND CONFIDENTIAL, ALL RIGHTS RESERVED**

ELEVATION VIEW  
(STAND-ALONE)

FB-2050  
Submittal Drawing

SHEET: 1 OF 6

20230227-10-M


SCALE: N.T.S.

# SLOAN FIXED BOLLARD M50/P2

SET & POUR BOLLARD - MODEL FB-2050

CRASH TESTED TO ASTM F2656-07 - M50/P2 RATED - STOPS 15,000 LB. VEHICLE AT 50 MPH IMPACT

## TYPICAL SINGLE BOLLARD INSTALLATION



6828 W Melrose St.  
Boise, ID 83709  
Phone: 1-800-275-5998  
Email: info@sloansg.com  
Web: www.sloansg.com

**PATENT PROTECTED**

**THE DRAWINGS AND INFORMATION CONTAINED HEREIN ARE  
PROPRIETARY AND CONFIDENTIAL, ALL RIGHTS RESERVED**

PLAN VIEW  
(STAND-ALONE)

FB-2050  
Submittal Drawing

SHEET: 2 OF 6

20230227-10-M

SCALE: N.T.S.

# SLOAN FIXED BOLLARD M50/P2


SET & POUR BOLLARD - MODEL FB-2050

CRASH TESTED TO ASTM F2656-07 - M50/P2 RATED - STOPS 15,000 LB. VEHICLE AT 50 MPH IMPACT

## TYPICAL BOLLARD ARRAY INSTALLATION

**KEY FEATURES:**

1. PREFABRICATED BOLLARD UNIT
2. NO REBAR IN FOUNDATION
3. BOLLARD SYSTEM CAN ACCOMMODATE TURNING RADIUS



**NOTE:**

1. MODIFIED SPACING FOR SITE SPECIFIC CONDITIONS AVAILABLE.

1/2" THICK 12" X 12" BASE PLATE WELDED TO BOTTOM OF BOLLARD  
 3" MASONRY BLOCKS OR CHAIRS TO ELEVATE BOLLARD STEEL OFF OF SUBGRADE



6828 W Melrose St.  
 Boise, ID 83709  
 Phone: 1-800-275-5998  
 Email: info@sloansg.com  
 Web: www.sloansg.com

**PATENT PROTECTED**

**THE DRAWINGS AND INFORMATION CONTAINED HEREIN ARE PROPRIETARY AND CONFIDENTIAL, ALL RIGHTS RESERVED**

ELEVATION VIEW  
(ARRAY)

FB-2050  
Submittal Drawing

SHEET: 3 OF 6

20230227-10-M


SCALE: N.T.S.

# SLOAN FIXED BOLLARD M50/P2

SET & POUR BOLLARD - MODEL FB-2050

CRASH TESTED TO ASTM F2656-07 - M50/P2 RATED - STOPS 15,000 LB. VEHICLE AT 50 MPH IMPACT

## TYPICAL BOLLARD ARRAY INSTALLATION



NOTE:  
1. MODIFIED SPACING FOR SITE SPECIFIC CONDITIONS AVAILABLE.



6828 W Melrose St.  
Boise, ID 83709  
Phone: 1-800-275-5998  
Email: info@sloansg.com  
Web: www.sloansg.com

PATENT PROTECTED

THE DRAWINGS AND INFORMATION CONTAINED HEREIN ARE  
PROPRIETARY AND CONFIDENTIAL, ALL RIGHTS RESERVED

PLAN VIEW  
(ARRAY)

FB-2050  
Submittal Drawing

SHEET: 4 OF 6

20230227-10-M

SCALE: N.T.S.

# SLOAN FIXED BOLLARD M50/P2


SET & POUR BOLLARD - MODEL FB-2050

CRASH TESTED TO ASTM F2656-07 - M50/P2 RATED - STOPS 15,000 LB. VEHICLE AT 50 MPH IMPACT


## MATERIALS PROVIDED

STANDARD FINISH:  
BLACK PAINT

### PREFABRICATED BOLLARD MATERIALS PROVIDED BY SLOAN SECURITY GROUP



(QTY 1) EACH:  
BOLLARD ASSEMBLY



PRE-CUT #8 REBAR  
@ 68" LONG  
QTY: FOUR (4) PER BOLLARD  
(INSIDE BOLLARD)

### MATERIALS PROVIDED BY INSTALLER

1. CONCRETE, 2.7 CUBIC YARDS PER BOLLARD
2. CHAIRS TO ELEVATE BOLLARDS ABOVE SUBGRADE

**PATENT PROTECTED**

**THE DRAWINGS AND INFORMATION CONTAINED HEREIN ARE  
PROPRIETARY AND CONFIDENTIAL, ALL RIGHTS RESERVED**

MATERIALS  
PROVIDED

FB-2050  
Submittal Drawing

SHEET: 5 OF 6

20230227-10-M

SCALE: N.T.S.



6828 W Melrose St.  
Boise, ID 83709  
Phone: 1-800-275-5998  
Email: info@sloansg.com  
Web: www.sloansg.com

# SLOAN FIXED BOLLARD M50/P2

SET & POUR BOLLARD - MODEL FB-2050

CRASH TESTED TO ASTM F2656-07 - M50/P2 RATED - STOPS 15,000 LB. VEHICLE AT 50 MPH IMPACT

## INSTALLATION STEPS


① EXCAVATE THEN TAMP SUBGRADE WITH PLATE TAMPER.

② USE MASONRY BLOCK OR CHAIRS TO ELEVATE BOLLARD OFF SUBGRADE, SO THAT TOP OF GUSSET / SLEEVE IS SAME HEIGHT AS TOP OF CONCRETE.

③ PLACE PREFABRICATED BOLLARDS INTO EXCAVATION.

④ INSERT VERTICAL REBAR INTO BOLLARD TUBE.

⑤ FILL BOLLARD TUBE AND EXCAVATION WITH CONCRETE.



6828 W Melrose St.  
Boise, ID 83709  
Phone: 1-800-275-5998  
Email: info@sloansg.com  
Web: www.sloansg.com

**PATENT PROTECTED**

**THE DRAWINGS AND INFORMATION CONTAINED HEREIN ARE  
PROPRIETARY AND CONFIDENTIAL, ALL RIGHTS RESERVED**

INSTALLATION STEPS

FB-2050  
Submittal Drawing

SHEET: 6 OF 6

20230227-10-M

SCALE: N.T.S.